

Claims

1. A tool holding device comprising a first rail and a second rail vertically and horizontally offset from each other forming an opening therebetween for receiving an elongate member in a generally vertical orientation.

2. A device according to claim 1 wherein the rails comprise generally parallel crossbars further characterized by generally opposed edges for contacting the elongate member when inserted therebetween.

3. A device according to claim 2 further characterized by at least one depression formed along the opposed edges in the crossbars.

4. A device according to claim 3 further characterized by a second depression formed along the opposed edges in the crossbars.

5. A device according to claim 4 wherein the depressions are formed in both of the opposed edges and are generally aligned, thereby restricting movement of the elongate member when disposed therein.

6. A device according to claim 2 further comprising two end plates attached to side edges of the crossbars, whereby the end plates and the crossbars form a stable structure.

7. A device according to claim 6 wherein outward extents of the end plates define a footprint and wherein a vertical projection through a center of gravity of an elongate member inserted between the crossbars lies within the footprint.

8. A device according to claim 1 further comprising at least one elongate member inserted between the rails, the elongate member including a support for supporting an item thereon.

9. A device according to claim 8 further comprising a shelf disposed on the support.

1 10. A device according to claim 1 wherein the first rail and the second rail comprise a first
2 hoop and a second hoop generally concentric therewith, further wherein the first hoop and the
3 second hoop comprise generally opposed edges for contacting the elongate member when
4 inserted therebetween.

1 11. A device according to claim 10 further characterized by at least one depression formed
2 along the opposed edges in the hoops.

1 12. A device according to claim 11 further characterized by a second depression formed
2 along the opposed edges in the hoops.

1 13. A device according to claim 12 wherein the depressions are formed in both of the
2 opposed edges and are generally aligned, thereby restricting movement of the elongate member
3 when disposed therein.

1 14. A device according to claim 13 further comprising at least one leg attached to the hoops,
2 thereby forming a stable structure.

1 15. A device according to claim 14 wherein an outward extent of the at least one leg defines
2 a footprint, wherein a vertical projection through a center of gravity of an elongate member
3 inserted between the hoops lies within the footprint.

1 16. A method for storing elongate members comprising the steps of:
2 providing a first rail and a second rail vertically and horizontally offset from each other
3 forming an opening therebetween for receiving an elongate member in a generally vertical
4 orientation; and
5 inserting an elongate member between the rails.

1 17. A method according to claim 16 wherein the rails comprise generally opposed edges for
2 contacting the elongate member when inserted therebetween.

1 18. A method according to claim 17 further characterized by at least one depression formed
2 along the opposed edges in the rails.

1 19. A method according to claim 18 further characterized by a second depression formed
2 along the opposed edges in the rails.

1 20. A method according to claim 19 wherein the depressions are formed in both of the
2 opposed edges and are generally aligned, thereby restricting movement of the elongate member
3 when disposed therein.

add
A.5

add
B.3

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100